

LR-60



Low-Mid Rise Lifts

SKU# 5175729

6,000-lb. Capacity / Low-Rise Lift

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363

Monday - Friday, 7AM to 4:30PM PST

BendPak's Low-Rise Lifts are Your Solution for Quick Service

When you need a [low-rise lift](#) to add versatility and productivity to your shop or garage, your first stop should always be BendPak. Simple, safe and rugged, this rubber-topped low rise lift can handle a mighty 6,000-lb. load without hogging your precious floor space. Plus, it happily fits into narrower bays. The LR-60 is the ideal solution for quick service on today's passenger cars and light trucks. With wide rubber pads, wheel service and auto-body repair can now be performed on a surprisingly large variety of vehicles.

Features

- Portable version available
- Electric / hydraulic power system
- Multi-position safety locks
- Rubber lifting blocks included
- Dropped cross bar for added clearance
- Heavy-duty steel channel frame

Specifications

Lifting Capacity	6,000 lbs. (2,724 kg)
Lifting Cap. (Front)	3,000 lbs. (1,361 kg)
Lifting Cap. (Rear)	3,000 lbs. (1,361 kg)
Lift Height	23" (584 mm)
Lift Height + Blocks	24.5" (622 mm)
Lift Height + Optl. 3" Blocks	26" (661 mm)
Overall Pad Length	53" (1,346 mm)
Overall Length	82" (2,083 mm)
Overall Width	70.5" (1,791 mm)
Lowered Height	3.5" (89 mm)
Lifting Time	35 sec
Motor (*)	110 VAC / 50-60 Hz / 1 Ph
Lift Pad Dimensions	18" x 52" (457 mm x 2,591 mm)
Shipping Weight	814 lbs. (370 kg)
Shipping Dimensions	82" x 70" x 20" (2,083 mm x 1,778 mm x 508 mm)



Not all BendPak lift models meet the standards as prescribed by ANSI/ALI ALCTV-2017 or ANSI/UL 201. Consult www.autolift.org for complete listings or contact BendPak via contact@bendpak.com.