

MDS-6EXT



Low-Mid Rise Lifts

SKU# 5175192

6,000-lb. Cap. / Mid-Rise Lift / Extended Platform / Open Center

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363

Monday - Friday, 7AM to 4:30PM PST

Extended-Length Mid-Rise Lift for Longer Wheelbases

Using long-wheelbase vehicles as our point of reference, we designed the MDS-6EXT [mid-rise lift](#) to accommodate longer lifting points that better reach the extreme edges of the vehicle underbody. Along with the flush-mount MDS-6EXTF, these two extended mid-rise lift models maintain their open-center design, just like our standard length MDS-6LP and MDS-6LPF models.



Features

- 6,000-lb. lifting capacity
- Open-center design
- Adjustable arm assemblies
- Solid-steel safety lock bars
- Multiple lock positions
- Hinge-point with Zerk grease fittings
- Low-profile design
- Rubber blocks included
- Removable ramps

Specifications

Lifting Capacity	6,000 lbs. (2,724 kg)
Lift Height w/o Blocks	36.75" (934 mm)
Lift Height + Blocks	38.25" (972 mm)
Lift Platform Dimensions	19" x 78.7" (484 mm x 2,000 mm)
Width Between Platforms	40" to 46" (1,018 mm to 1,168 mm)
Overall Width	19" (484 mm)
Overall Length	104.3" (2,650 mm)
Lowered Height	5.25" (133 mm)
Lifting Time	35 sec
Motor (*)	110-220 VAC / 60 Hz / 1 Ph

* Special voltage available on request.

Design, materials, and specifications shown here are subject to change without notice.

Note: An air supply (minimum 50 psi / 10 CFM) is required for the safety-lock mechanisms to disengage. It is solely your responsibility to install and maintain the air supply.

Not all BendPak lift models meet the standards as prescribed by ANSI/ALI ALCTV-2017 or ANSI/UL 201. Consult www.autolift.org for complete listings or contact BendPak via contact@bendpak.com.