

Full-Rise Scissor Lifts

SKU# 5175424

7,000-lb. Capacity / Scissor Lift / Frame Engaging

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363

Monday - Friday, 7AM to 4:30PM PST

The Full-Rise Scissor Lift with Collapsible Frames

This space saving, frame engaging lift features no cross members whatsoever, making installation simpler than ever. It easily accommodates most passenger vehicles and light trucks, and it comes complete with pneumatic safety locks, rubber lifting blocks and an open center for full under car accessibility.

Features

- 7,000-lb. lifting capacity
- Pneumatic safety locks
- Hardened pivot pins with "Zerk" fittings
- Open-center design
- Ergonomic controls
- Dual-cylinder hydraulic design provides extra power
- Low-profile
- Surface-mount



Specifications

Lifting Capacity 7,000 lbs. (3,175 kg)**Max. Lifting Height** 70.5" (1,791 mm)**Overall Length** 165" (4,190 mm)**Overall Width - Min** 81.5" (2,072 mm)**Overall Width - Max** 87.5" (2,222 mm)**Single Platform Length** 62.5" (1,590 mm)**Single Platform Width** 22" (554 mm)**Lowered Height** 6.5" (165 mm)**Lifting Time** 45 sec**Standard Motor** 208-240 VAC / 50-60 Hz / 1 Ph

Note: An air supply (minimum 30 psi / 3 CFM) is required for the safety-lock mechanisms to disengage. It is solely the responsibility of the end-user to provide, install and maintain the air supply.

Not all BendPak lift models meet the standards as prescribed by ANSI/ALI ALCTV-2017 or ANSI/UL 201. Consult www.autolift.org for complete listings or contact BendPak via contact@bendpak.com.