

SP-7XEF

BendPak®

Full-Rise Scissor Lifts

SKU# 5175425

7,000-lb. Capacity / Scissor Lift / Frame Engaging / Flush Mount

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363

Monday - Friday, 7AM to 4:30PM PST

Flush-Mount Scissor Lift

This flush-mount version of our full-rise scissor lift is ideal for shops that are limited in space but have a huge demand for performance. The SP-7XEF has all the lifting height of a two-post lift without the columns that take up precious shop space. Features a 22" x 63" lift platform, equalization torsion bar, hardened pivot pins, dual hydraulic cylinders and ergonomic controls.

Features

- 7,000-lb. lifting capacity
- Pneumatic safety locks
- Hardened pivot pins with "Zerk" fittings
- Open-center design
- Ergonomic controls
- Dual-cylinder hydraulic design provides extra power
- Low-profile



Specifications

Lifting Capacity 7,000 lbs. (3,175 kg)

Max. Lifting Height 70.5" (1,791 mm)

Overall Length 105.5" (2,692 mm)

Overall Width - Min 81.5" (2,072 mm)

Overall Width - Max 87.5" (2,222 mm)

Single Platform Length 62.5" (1,590 mm)

Single Platform Width 22" (554 mm)

Lowered Height Flush with concrete

Lifting Time 45 sec

Standard Motor 208-240 VAC / 50-60 Hz / 1 Ph

Note: An air supply (minimum 30 psi / 3 CFM) is required for the safety-lock mechanisms to disengage. It is solely the responsibility of the end-user to provide, install and maintain the air supply.

Not all BendPak lift models meet the standards as prescribed by ANSI/ALI ALCTV-2017 or ANSI/UL 201. Consult www.autolift.org for complete listings or contact BendPak via contact@bendpak.com.

BendPak®



30440 Agoura Road Agoura Hills, CA 91301 USA

© 2023 BendPak Inc. All rights reserved.