

E1.2B3F1



Hydraulic Power Units

SKU# 5585435

1.6 Gal Reservoir, 2,500 PRV, 1.5 HP Motor, 110-230V / 50-60 Hz / 1 Ph, CE Approved

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363

Monday - Friday, 7AM to 4:30PM PST

This Hydraulic Power Unit is Totally CE Approved

If you're looking for a [hydraulic power unit](#) with a compact tank that still offers enough juice to lift a 10,000-lb. truck or SUV, you're in the right place. The E1.2B3F1 hydraulic power pack is designed with a generous 2,500 PRV, which means the unit can handle higher hydraulic pressure buildup in the unlikely event that the fluid back-pressure exceeds normal operating conditions. When used on a low-rise car lift, your car will be lifted to the lift's max capacity in just 30 seconds.

Features

- High mechanical and volumetric efficiency
- End head prepared for lift-hold-lower applications using our manual lowering valve or solenoid cartridge valves.
- Totally enclosed motors are suitable for use in humid environments or dusty, contaminated atmospheres. UL Recognized AC electric motors feature heavy gauge steel frame and high-quality ball bearings.
- Torque load remains constant throughout operation.
- Heavy-duty start switches with a high IP-protection class and silver-plated contacts for a long service life.
- Cartridge-style relief valves meet tough demands for dependability and life expectancy.
- Minimum recommended temperature is -25°C (-13°F).
- Maximum recommended temperature is +80°C (+175°F).
- 12-months warranty

Specifications

SKU#	Model	Reservoir	PRV	HP	Cert
5585280	F2.1F3H1	3.6 gal	2,850	2.5	UL/ETL
5585285	E2.1F3H1	3.6 gal	2,650	2.5	UL/ETL
5585315	E0.8B8F1	1.6 gal	1,900	1.5	UL/ETL
5585320	E3.7K3H2	8.5 gal	2,400	2.5	UL/ETL
5585325	F3.2G3H1	4.2 gal	2,650	2.5	UL/ETL
5585435	E1.2B3F1	1.6 gal	2,500	1.5	CE

