

E3.7K3H2



Hydraulic Power Units

SKU# 5585320

8.5 Gal Reservoir, 2,400 PRV, 2.5 HP Motor, 208-230V /
50-60 Hz / 1 Ph, UL/ETL Listed

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363

Monday - Friday, 7AM to 4:30PM PST

Made to Last the Lifespan of Any Car Lift

We took our [hydraulic power unit](#) with the largest motor and redesigned an 8.5-gallon tank for it. More fluid means more pressure can be exerted counter to the weight of a heavy vehicle. The heaviest commercial trucks and SUVs that our car lifts can handle can be serviced by this hydraulic power unit. Keep in mind, this particular unit's 2,400 psi pressure relief valve is specially optimized to handle high-pressure situations, so you're always covered when lifting.

Features

- High mechanical and volumetric efficiency
- End head prepared for lift-hold-lower applications using our manual lowering valve or solenoid cartridge valves.
- Totally enclosed motors are suitable for use in humid environments or dusty, contaminated atmospheres. UL Recognized AC electric motors feature heavy gauge steel frame and high-quality ball bearings.
- Torque load remains constant throughout operation.
- Heavy-duty start switches with a high IP-protection class and silver-plated contacts for a long service life.
- Cartridge-style relief valves meet tough demands for dependability and life expectancy.
- Minimum recommended temperature is -25°C (-13°F).
- Maximum recommended temperature is +80°C (+175°F).
- 12-months warranty

Specifications

SKU#	Model	Reservoir	PRV	HP	Cert
5585280	F2.1F3H1	3.6 gal	2,850	2.5	UL/ETL
5585285	E2.1F3H1	3.6 gal	2,650	2.5	UL/ETL
5585315	E0.8B8F1	1.6 gal	1,900	1.5	UL/ETL
5585320	E3.7K3H2	8.5 gal	2,400	2.5	UL/ETL
5585325	F3.2G3H1	4.2 gal	2,650	2.5	UL/ETL
5585435	E1.2B3F1	1.6 gal	2,500	1.5	CE

